

Rolls



OPzV GEL DEEP CYCLE BATTERY

S2-920GEL



Series	GEL	Warranty	See Warranty Terms
Volts	2	BCI	2V OPzV
Cells	1		
Terminal Type		F10	
Included Hardware		Threaded Insert & Bolt	
Size & Thread		F10-M10	

Charge

Recommended Charge Current	80 A
Maximum Charge Current	240 A
Self-Discharge Rate	Less than 2% per month at 20°C (68°F)
Internal Resistance	0.34 mΩ

Capacity

Capacity Affect by Temperature	40°C (104°F)	25°C (77°F)	0°C (32°F)	-15°C (5°F)
	105%	100%	89%	79%

Hour Rate	Capacity / AMP Hour	Current / AMPs
@ 100 Hour Rate	1287 AH	12.87 A
@ 20 Hour Rate	1046 AH	52.3 A
@ 10 Hour Rate	920 AH	92 A

Specifications




SAI GLOBAL
ISO 9001
Quality

Weight	65.5 kg	144.5 lbs
Length	19.1 cm	7.52"
Width	21 cm	8.27"
Height Inc. Term.	67.3 cm	26.5"

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process, battery components & electrolyte levels.

Container	ABS
Cover	ABS
Handles	None

Cycle Life vs. Depth of Discharge



Capacity vs. Temperature

